## MODEL P05-1500X1000

Double flat bed press used for:

- · Transfer printing
- · Thermosetting heatsetting
- · Film/web thermobonding
- · Plastification and coating with film
- · Metallization and gold lamination
- · Transfer of special effects (es.: snake skin)
- 1. Characteristic of printing planes:
- 1.1. Planes number: 2
- 1.2. Dimensions: 1.500 mm (59,06") x 1.000 mm (39,37")
- 1.3. Working dimensions normal printing: 1.450 mm (57") x 950 mm (37.5")
- 2. Heating and temperature control:
- 2.1. The printing plane is heated by electrical resistors.
- 2.2. The temperature of the printing plane is adjustable up to 230°C and controlled by electronic thermostat.
- 3. Other devices into machine:
- 3.1. Motorized semi-automatic functions
- 3.2. Motorized movement of working planes
- 3.3. Automatic and recordable stroke times
- 3.4. Hydraulic pressure
- 4. Technical data:
- 4.1. Installed power: 10.5 kW
- 4.2. Average electrical consumption: 6,5 kW
- 4.3. Overall dimensions: width 1.965 mm (77,5 "). length 2.410 mm (95"). height 1.335 mm (52,5").
- 4.4. Net weight: 1.175 kg
- 4.5. Machine produced according to CE rules
- 4.6. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



LindenmeyrMunroe.com



## MODEL P05-1500X1000

Double flat bed press used for:

- · Transfer printing
- · Thermosetting heatsetting
- · Film/web thermobonding
- · Plastification and coating with film
- · Metallization and gold lamination
- · Transfer of special effects (es.: snake skin)
- 1. Characteristic of printing planes:
- 1.1. Planes number: 2
- 1.2. Dimensions: 1.500 mm (59,06") x 1.000 mm (39,37")
- 1.3. Working dimensions normal printing: 1.450 mm (57") x 950 mm (37.5")
- 2. Heating and temperature control:
- 2.1. The printing plane is heated by electrical resistors.
- 2.2. The temperature of the printing plane is adjustable up to 230°C and controlled by electronic thermostat.
- 3. Other devices into machine:
- 3.1. Motorized semi-automatic functions
- 3.2. Motorized movement of working planes
- 3.3. Automatic and recordable stroke times
- 3.4. Hydraulic pressure
- 4. Technical data:
- 4.1. Installed power: 10.5 kW
- 4.2. Average electrical consumption: 6,5 kW
- 4.3. Overall dimensions: width 1.965 mm (77,5 "). length 2.410 mm (95"). height 1.335 mm (52,5").
- 4.4. Net weight: 1.175 kg
- 4.5. Machine produced according to CE rules
- 4.6. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



LindenmeyrMunroe.com



## MODEL P05E-1500X1000

Double flat bed press used for:

- · Transfer printing
- · Thermosetting heatsetting
- · Film/web thermobonding
- · Plastification and coating with film
- · Metallization and gold lamination
- · Transfer of special effects (es.: snake skin)
- 1. Characteristic of printing planes:
- 1.1. Planes number: 2
- 1.2. Dimensions: 1.500 mm (59,06") x 1.000 mm (39,37")
- 1.3. Working dimensions normal printing: 1.450 mm (57") x 950 mm (37,5")
- 2. Heating and temperature control:
- 2.1. The printing plane is heated by electrical resistors.
- 2.2. The temperature of the printing plane is adjustable up to 230°C and controlled by electronic thermostat
- 3. Other devices into machine:
- 3.1. Motorized semi-automatic functions
- 3.2. Automatic and recordable stroke times
- 3.3. Hydraulic pressure
- 4. Technical data:
- 4.1. Installed power: 10.5 kW
- 4.2. Average electrical consumption: 7 kW/h
- 4.3. Overall dimensions: width 2.060 mm (81"). length 2.410 mm (95"). height 1.210 mm (48").
- 4.4. Net weight: 890 kg
- 4.5. Machine produced according to CE rules
- 4.6. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



